

What is claimed is:

1. A vehicle lamp comprising:

first and second lamp chamber portions each including:

5 a light source; a casing having an opening and a portion for reflecting a light emitted from the light source; and a lens portion for closing the opening; the first and second lamp chamber portions each forming a lamp chamber partitioned with the casing and the lens portion,

10 wherein the lens portion of the first lamp chamber portion passes light through forwardly or backwardly from a vehicle;

at least a part of the second lamp chamber portion disposed within the lamp chamber of the first lamp chamber portion; and

15 the second lamp chamber portion overlapped with the light source of the first lamp chamber portion in the substantially longitudinal direction.

2. The vehicle lamp as set forth in claim 1, wherein

20 a surface treatment for reflecting the light is applied on an exterior surface of the second lamp chamber portion facing to the light source of the first lamp chamber portion.

3. The vehicle lamp as set forth in claim 1, wherein

25 the casing of the second lamp chamber portion is formed of a half-mirror.

4. The vehicle lamp as set forth in claim 1, wherein
the lens portion of the first lamp chamber portion is
formed of a clear lens, and at least said part of the lens portion
5 of the second lamp chamber portion is formed of a diffusion
lens for diffusing said light within the lamp chamber of the
second lamp chamber portion.

5. The vehicle lamp as set forth in claim 2, wherein
10 the lens portion of the first lamp chamber portion is
formed of a clear lens, and at least said part of the lens portion
of the second lamp chamber portion is formed of said diffusion
lens for diffusing said light within the lamp chamber of the
second lamp chamber portion.

15 6. The vehicle lamp as set forth in claim 3, wherein
the lens portion of the first lamp chamber portion is
formed of a clear lens, and at least said part of the lens portion
of the second lamp chamber portion is formed of said diffusion
20 lens for diffusing said light within the lamp chamber of the
second lamp chamber portion.

7. The vehicle lamp as set forth in claim 1, wherein
a projected shielding portion for obstructing a direct
25 incidence of the light emitted from the light source of the

first lamp chamber portion on the lens portion of the second lamp chamber portion is formed on the exterior surface of the second lamp chamber portion.

5 8. The vehicle lamp as set forth in claim 5, wherein
said projected shielding portion for obstructing said
direct incidence of the light emitted from the light source
of the first lamp chamber portion on the lens portion of the
second lamp chamber portion is formed on the exterior surface
10 of the second lamp chamber portion.

 9. The vehicle lamp as set forth in claim 6, wherein
said projected shielding portion for obstructing said
direct incidence of the light emitted from the light source
15 of the first lamp chamber portion on the lens portion of the
second lamp chamber portion is formed on the exterior surface
of the second lamp chamber portion.

 10. The vehicle lamp as set forth in claim 1, wherein
20 a slit for guiding the light emitted from the light source
of the first lamp chamber portion to said part of the lens portion
of the second lamp chamber portion is formed in the casing of
the second lamp chamber portion.

25 11. The vehicle lamp as set forth in claim 8, wherein

a slit for guiding the light emitted from the light source of the first lamp chamber portion to said part of the lens portion of the second lamp chamber portion is formed in the casing of the second lamp chamber portion.

5

12. The vehicle lamp as set forth in claim 9, wherein said slit for guiding the light emitted from the light source of the first lamp chamber portion to said part of the lens portion of the second lamp chamber portion is formed in the casing of the second lamp chamber portion.

13. The vehicle lamp as set forth in claim 1, wherein the second lamp chamber portion is disposed so as to cross over the inside of the lamp chamber of the first lamp chamber portion.

14. The vehicle lamp as set forth in claim 11, wherein the second lamp chamber portion is disposed so as to cross over the inside of the lamp chamber of the first lamp chamber portion.

15. The vehicle lamp as set forth in claim 12, wherein the second lamp chamber portion is disposed so as to cross over the inside of the lamp chamber of the first lamp chamber portion.